

# B-MOUNT SERIES:

## Load Range (B-Series) & "H" Dimensions

CUP TYPE					
Flat Core	Dimple Core	Height	Max. S.A Def.	Weight	Max. Static Load
B22-BC-0.5 B22-BC-1.0 B22-BC-2.0 B22-BC-3.0	Not Available	1.17"	.25"	.05 lbs.	0.5 lbs. 1.0 lbs. 2.0 lbs. 3.0 lbs.
B44-EB-1 B44-EB-2 B44-EB-4 B44-CB-6 B44-CB-10	B44-DB-1 B44-DB-2 B44-DB-4 B44-BB-6 B44-BB-10	1.58"	.25"	.16 lbs.	1.0 lbs. 2.0 lbs. 4.0 lbs. 6.0 lbs. 10.0 lbs.
B64-CB-5 B64-CB-10 B64-CB-20 B64-CB-40	B64-BB-5 B64-BB-10 B64-BB-20 B64-BB-40	1.53"	.25"	.44 lbs.	5.0 lbs. 10.0 lbs. 20.0 lbs. 40.0 lbs.
PLATE TYPE					
B21-BC-0.5 B21-BC-1.0 B21-BC-2.0 B21-BC-3.0	Not Available	.55"	.25"	.05 lbs.	0.5 lbs. 1.0 lbs. 2.0 lbs. 3.0 lbs.
B43-EB-1 B43-EB-2 B43-EB-4 B43-CB-6 B43-CB-10	B43-DB-1 B43-DB-2 B43-DB-4 B43-DB-6 B43-DB-10	.67"	.25"	.16 lbs.	1.0 lbs. 2.0 lbs. 4.0 lbs. 6.0 lbs. 10.0 lbs.

B64 Series Core				
Designation	Core Material	Core Thread	Core C' Sink $\phi$	
BA	SST	COARSE	0.562	Dimple
CA	SST	COARSE	0.281	Flat
DA	SST	FINE	0.562	Dimple
EA	SST	FINE	0.281	Flat
BB	ALUM	COARSE	0.562	Dimple
CB	ALUM	COARSE	0.281	Flat
DB	ALUM	COARSE	0.562	Helicoil/Flat
EB	ALUM	FINE	0.281	Flat
FB	ALUM	FINE	0.652	Dimple

B43 & B44 Series Cores				
Designation	Core Material	Core Thread	Core C' Sink $\phi$	
BB	SST	COARSE	0.437	Dimple
CB	SST	COARSE	0.172	Flat
DB	SST	COARSE	0.437	Dimple
EB	SST	COARSE	0.172	Flat
BC	ALUM	COARSE	0.437	Dimple
CC	ALUM	COARSE	0.172	Flat
DC	ALUM	COARSE	0.437	Dimple
EC	ALUM	COARSE	0.172	Flat

